

EPJD-SLG021

L'éclairage solaire led urbain EPJD-SLG021 est un éclairage à haute performance. A la pointe de la technologie LED, pour plus de performance et d'efficacité, avec sa conception solaire, il est idéal pour une installation hors réseau électrique, conçu pour maximiser les performances d'éclairage. Il optimisera les stratégies d'économies circulaires, tout en limitant l'empreinte carbone. Ce produit convient pour l'éclairage routier, urbain, parc et jardin.

DÉTAILS DU PRODUIT



Product Code	EPJD-SLG021A	EPJD-SLG021B	EPJD-SLG021C	EPJD-SLG023A	EPJD-SLG023B	EPJD-SLG023C
LED Quantity	120pcs 3030	120pcs 3030	120pcs 3030	120pcs 3030	120pcs 3030	120pcs 3030
Rate Power	10W	15W	20W	10W	15W	20W
Color Temperature	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K
Color	black	black	black	black	black	black
Charge time	4-5hours	5-6hours	6-7hours	4-5hours	5-6hours	6-7hours
Discharge time	8hours(full power)	8hours(full power)	8hours(full power)	8hours(full power)	8hours(full power)	8hours(full power)
Operating time	Intelligent dimming model 4-6 days	Intelligent dimming model 4-6 days	Intelligent dimming model 4-6 days	Intelligent dimming model 4-6 days	Intelligent dimming model 4-6 days	Intelligent dimming model 4-6 days
Luminary EER	1800lm/6500K	2600lm/6500K	3600lm/6500K	1800lm/6500K	2600lm/6500K	3600lm/6500K
Color Temperature	RA75	RA75	RA75	RA75	RA75	RA75
Battery capacity	8AH	12AH	16AH	8AH	12AH	16AH
Battery type	IFR lithium iron phosphate	IFR lithium iron phosphate	IFR lithium iron phosphate	IFR lithium iron phosphate	IFR lithium iron phosphate	IFR lithium iron phosphate
Solar monocrystalline silicon panel	39W	39W	39W	39W	39W	39W
Installation Pipe Dia	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm	Φ60mm/Φ76mm
Installation Height	3-5m	3-5m	3-5m	3-5m	3-5m	3-5m
Temperature of working condition	-10°C – 60°C	-10°C – 60°C	-10°C – 60°C	-10°C – 60°C	-10°C – 60°C	-10°C – 60°C
humidity of working condition	20%-90%	20%-90%	20%-90%	20%-90%	20%-90%	20%-90%
LED life time	70000h	70000h	70000h	70000h	70000h	70000h
Profestion Grade	IP66	IP66	IP66	IP66	IP66	IP66
Net Weight	10.05 kg	10.45 kg	11.85 kg	11.55kg	11.95 kg	12.35 kg
Gross Weight	11.55 kg	11.95 kg	13.05 kg	13.05kg	13.45 kg	13.85 kg
Product Size	602*602*177mm	602*602*177mm	602*602*177mm	602*602*599mm	602*602*599mm	602*602*599mm
Packing Size	635*635*220mm bracket assembled			755*635*120mm	755*635*120mm	755*635*120mm

