

# EPJD-G031

L'éclairage led urbain EPJD-G031 domine jusqu'à 5 m de hauteur, ce produit futuriste impose la délicatesse de ses courbes et séduit par sa prestance.

Son corps est réalisé en aluminium. Son bloc optique en verre polycarbonate est IK08 et constitue un ensemble étanche IP66.

## DÉTAILS DU PRODUIT



Product Code	EPJD-G031A	EPJD-G031B	EPJD-G031C
Electric Current	75mA	100mA	110mA
LED Quantity	16pcs 5050	24pcs 5050	36pcs 5050
Rate Power	30W	60W	100W
Color Temperature	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K
Luminous Flux	2700lm/4000K	5400lm/4000K	6000lm/4000K
Input Voltage	AC100-240V	AC100-240V	AC100-240V
Frequency Range	50/60Hz	50/60Hz	50/60Hz
Color Temperature	RA75	RA75	RA75
Temperature of working condition	-40°C - 50°C	-40°C - 50°C	-40°C - 50°C
Humidity of working condition	20%-90%	20%-90%	20%-90%
LED life time	70000h	70000h	70000h
Protection Grade	IP66	IP66	IP66
Installation Pipe Dia	Ø76mm	Ø76mm	Ø76mm
Installation Height	3-5m	4-6m	7-9m
Net Weight	7.9kg	8.46kg	8.5kg
Gross Weight	9.1kg	9.66kg	10.5kg
Product Size	517*517*147mm	517*517*147mm	517*517*147mm

