

# EPJD-G032

L'éclairage led urbain EPJD-G032 est un luminaire multifonctions en forme de cône renversé pour éclairage direct ou indirect. Corps en fonte d'aluminium composé de deux pièces principales en tête, d'une doucine. Vasque en verre clair, optique en aluminium brillant anodisé et globe en Pmma ou polycarbonate. Fixation sur mât 76mm.

## DÉTAILS DU PRODUIT



Product Code	EPJD-G032A	EPJD-G032B	EPJD-G032C
Electric Current	75mA	100mA	110mA
LED Quantity	16pcs 5050	24pcs 5050	36pcs 5050
Rate Power	30W	60W	100W
Color Temperature	6500/4000/3000K	6500/4000/3000K	6500/4000/3000K
Luminous Flux	2700lm/4000K	5400lm/4000K	6000lm/4000K
Input Voltage	AC100-240V	AC100-240V	AC100-240V
Frequency Range	50/60Hz	50/60Hz	50/60Hz
Color Temperature	RA75	RA75	RA75
Temperature of working condition	-40°C - 50°C	-40°C - 50°C	-40°C - 50°C
Humidity of working condition	20%-90%	20%-90%	20%-90%
LED life time	70000h	70000h	70000h
Protection Grade	IP66	IP66	IP66
Installation Pipe Dia	Φ76mm	Φ76mm	Φ76mm
Installation Height	3-5m	4-6m	7-9m
Net Weight	7.9kg	8.46kg	8.5kg
Gross Weight	9.1kg	9.66kg	10.5kg
Product Size	517*517*300mm	517*517*300mm	517*517*300mm

